



Standards

- Designed to meet BS1726, class B.
- Springs powder coated.

Description

- Closed Spring Mount design provides horizontal stability, high loading capacity and protective spring enclosure.
- All mounts have external levelling arrangement, capable of compensating for full static deflection.
- Inner walls of lower casing have resilient rubbers nubbars.
- Deflection is at rated load with 15% tolerance.
- All mounts have approximately 50% overload capacity.
- Mountings must be adjusted so that upper housing clear slower housing by at least 6 mm and not more than 12 mm.
- Application examples include : Chiller, AHU's, pumps, centrifugal / axial fans' condensing units, roof top packaged units, reciprocating compressors, DG sets, punch presses, drop hammers, and floor pipe supports (normally at first few pipe support points leading from isolated equipment.)

Technical Data

Item Code	Art. No.	Color Code	Bolt	L	B	s	R	k	FH	Deflection	Max. Load
				mm	mm	mm	mm	mm	mm	mm	N
SP CSM 60	4422560	Yellow	M12	160	92	5	M10	147	116	25	600
SP CSM 100	44225100	Black	M12	160	92	5	M10	147	116	25	1000
SP CSM 160	44225160	White	M12	160	92	5	M10	147	116	25	1600
SP CSM 200	44225200	Green	M12	160	92	5	M10	147	116	25	2000
SP CSM 250	44225250	Blue	M12	160	92	5	M10	147	116	25	2500
SP CSM 300	44225300	Red	M16	200	115	10	M12	180	158	25	3000
SP CSM 400	44225400	Purple	M16	200	115	10	M12	180	158	25	4000
SP CSM 500	44225500	Grey	M16	200	115	10	M12	180	158	25	5000
SP CSM 600	44225 600	Green	M16	200	115	10	M12	180	158	25	6000
SP CSM 800	44225800	Blue	M16	200	115	10	M12	180	158	25	8000
SP CSM 1050	442251050	Yellow	M16	200	115	10	M12	180	158	25	10500
SP CSM 1250	442251250	Black	M16	200	115	10	M12	180	158	25	12500
SP CSM II/600	44325600	Red	M20	285	115	10	M16	265	163	25	6000
SP CSM II/800	44325800	Purple	M20	285	115	10	M16	265	163	25	8000
SP CSM II/1050	443251000	Grey	M20	285	115	10	M16	265	163	25	10500
SP CSM II/1200	443251200	Green	M20	285	115	10	M16	265	163	25	12000
SP CSM II/1600	443251600	Blue	M20	285	115	10	M16	265	163	25	16000
SP CSM II/2100	443252100	Yellow	M20	285	115	10	M16	265	163	25	21000
SP CSM II/2500	443252500	Black	M20	285	115	10	M16	265	163	25	25000
SP CSM IV/1200	444251200	Red	M20	285	210	10	M16	265	163	25	12000
SP CSM IV/1600	444251600	Purple	M20	285	210	10	M16	265	163	25	16000
SP CSM IV/2000	444252000	Grey	M20	285	210	10	M16	265	163	25	20000
SP CSM IV/2400	444252400	Green	M20	285	210	10	M16	265	163	25	24000
SP CSM IV/3200	444253200	Blue	M20	285	210	10	M16	265	163	25	32000
SP CSM IV/4200	444254200	Yellow	M20	285	210	10	M16	265	163	25	42000
SP CSM IV/5000	444255000	Black	M20	285	210	10	M16	265	163	25	50000

Note :

Due to policy of continual improvement, the specifications are subject to change without prior notice.

Measurement are subject to 5% tolerance.

To achieve good sound suppressions do not over load fitting.