



Properties

Standards

Electro galvanized as per ASTM B 633

Galvanized as per ASTM A 123/ A 123M

Designed to meet MSS Standard SP-58 2002, Type 44 and SP-69

Material

Bracket: Mild Steel

Roller: Mild Steel / Cast Iron

Finish

Electro Zinc Plated GI /
Hot dip galvanized HDG

Applications

- For support of pipe where horizontal movement due to expansion and contraction may occur.

Technical Data

Roller Stand (GI)

Item	Art No. for GI	Pipe Size (mm)	Pipe Size (inch)	Pipe Outer Dia. (mm)	Dimension P (mm)	Dimension Q (mm)	Dimension C x L (mm)	Bolt Dia. (mm)	Max. Load (N)
SRS 60	4300060	DN50	2"	60.3	100	40.0	M12 X 80	16.0	5500
SRS 73	4300073	DN65	2 1/2"	73.0	100	48.0	M12 X 90	16.0	5500
SRS 90	4300090	DN80	3"	88.9	100	55.0	M12 X 95	16.0	5500
SRS 101	4300101	DN90	3 1/2"	101.6	100	61.0	M12 X 100	16.0	5500
SRS 114	4300114	DN100	4"	114.3	115	72.0	M12 X 115	16.0	13000
SRS 141	4300141	DN125	5"	141.3	115	85.0	M12 X 130	16.0	13000
SRS 168	4300168	DN150	6"	168.3	125	100.0	M20 X 160	16.0	13000
SRS 219	4300219	DN200	8"	219.1	130	125.0	M24 X 190	20.0	17500
SRS 273	4300273	DN250	10"	273.1	130	155.0	M24 X 225	20.0	17500
SRS 323	4300323	DN300	12"	323.8	130	180.0	M24 X 260	20.0	35000
SRS 356	4300356	DN350	14"	355.6	130	197.0	M24 X 275	20.0	35000
SRS 406	4300406	DN400	16"	406.4	165	220.0	M24 X 300	24.0	52500
SRS 457	4300457	DN450	18"	457.2	165	250.0	M33 X 345	24.0	52500
SRS 508	4300508	DN500	20"	508.2	165	275.0	M33 X 370	24.0	52500
SRS 610	4300610	DN600	24"	609.6	190	330.0	M52 X 480	24.0	65000
SRS 661	4300661	DN650	26"	661.0	200	355.0	M52 X 500	30.0	84500
SRS 712	4300712	DN700	28"	712.0	200	385.0	M52 X 530	30.0	84500
SRS 755	4300755	DN750	30"	755.0	200	405.0	M52 X 550	30.0	84500

Note: Hot Dip Galvanized Finishes are available upon request.